



ALUMINUM WOOD SYSTEMS

FEATURING 2 1/4" THICK PANELS, THE **ALUMINUM WOOD** SYSTEM DELIVERS EVERYTHING YOU DEMAND IN A CLAD SYSTEM-LOW MAINTENANCE EXTERIOR WITH THE BEAUTY OF A REAL NATURAL WOOD INTERIOR, COMBINED WITH CONCEALED MULTI-POINT LOCKS.

THE **ALUMINUM WOOD** SERIES FEATURES & BENEFITS:

- SIGNATURE NARROW 3 5/8" STILE & RAIL UP TO 10' TALL
- HYBRID PANEL CONSTRUCTION OF 1 3/4" THICK EXTRUDED ALUMINUM AND 1/2" SOLID WOOD INTERIOR
- VERTICAL GRAIN DOUGLAS FIR AND MAHOGANY WOOD SPECIES IN-STOCK OR CUSTOM ORDER
 ANY SPECIES, INCLUDING FSC CERTIFIED WOODS

FEATURES

- CONCEALED MULTI-POINT LOCKING SYSTEM FOR EASE OF OPERATION, SECURITY & SINGLE ACTION LOCKING
- SIMULATED DIVIDING LITES (SDL) 1" SCULPTED PROFILE, AVAILABLE IN MOST TRADITIONAL & MODERN PATTERNS
- 1/4" SINGLE TO 1 1/4" TRIPLE GLAZING OPTIONS
- DISTINCTIVE WHITE AND BRONZE IN-STOCK FINISHES OR CUSTOM KYNAR OR POWDERCOAT TO VIRTUALLY ANY COLOR
- STYLISH DAILY DOOR HANDLE TRIMSET AND LOCK INCLUDED
- PERFECT FOR BOTH CONTEMPORARY AND TRADITIONAL ARCHITECTURAL DESIGNS
- REAL WOOD LOOK POWDERCOAT EXTERIOR FOR AN ALL WOOD LOOK
- ENGINEERED ALUMINUM PANEL CONSTRUCTION BETTER SUITED TO HARSH ENVIRONMENTS
 THAN A SOLID WOOD DOOR

BENEFITS

- STRENGTH AND RIGIDITY FOR PANELS OVER 8'TALL
- WIDE RANGE OF GLAZING OPTIONS FOR IMPROVED THERMAL PERFORMANCE, SAFETY PROTECTION AND IMPACT RESISTANCE
- COMBINE WITH OUR SCREEN OR BLIND SYSTEM FOR THE ULTIMATE GLASS AND VENTILATING WALL

Lacantina doors systems are built to last and feature the highest quality hardware FOR EFFORTLESS PERFORMANCE. Lacantina doors folding hardware, handle and locks, are AVAILABLE IN STAINLESS STEEL AND BRONZE FINISHES.

HARDWARE







SUMMIT MULTI-POINT HANDLE BRONZE



TWIN BOLT LEVER STAINLESS STEEL



PULL HANDLE STAINLESS STEEL

PULL HANDLE BRONZE

DUAL GLAZED TEMPERED GLASS IS STANDARD ON ALL Lacantina door SYSTEMS. FOR BETTER ENERGY PERFORMANCE, WE FEATURE CARDINAL'S LOE GLASS INCLUDING LoE-272 AND LoE-366. MOST COMMERCIALLY AVAILABLE GLASS GLAZING CAN BE USED, INCLUDING TINTED, OBSCURE, LAMINATED AND SINGLE GLAZED. LAMINATED GLASS WITH SGP INTERLAYER CAN BE ADDED FOR SECURITY OR IMPACT PROTECTION. SHOULD YOUR PROJECT REQUIRE CUSTOMIZED GLASS PLEASE CONTACT US TO VERIFY AVAILABILITY.





WOOD

LaCANTINA DOORS COMPONENTS FEATURE LAMINATED ENGINEERED CORES FOR PERFORMANCE AND A GENEROUS LAYER OF SOLID STAIN-GRADE WOOD, LaCANTINA DOORS IS A TRUE FSC CHAIN OF CUSTODY MANUFACTURER.

Lacantina doors are available in 2 in-stock wood species.

IN-STOCK WOOD



CUSTOM WOOD

CUSTOM WOOD SPECIES ARE AVAILABLE UPON REQUEST. POPULAR SPECIES INCLUDE PINE, ALDER, OAK, MAPLE, CHERRY AND WALNUT.

COLORS

Lacantina doors offer a wide range of in-stock, optional and custom colors for the exterior and INTERIOR ALUMINUM OF YOUR BIFOLDING DOOR SYSTEM.

Lacantina doors folding doors systems are available in 2 in-stock colors:

IN-STOCK COLORS



Lacantina doors offer a wide range of 19 of the most popular colors in the marketplace today:



OPTIONAL COLORS*



CUSTOM COLORS*

A 2-COAT 70% KYNAR IS THE STANDARD FINISH. MULTI-COAT, METALLIC AND PREMIUM POWDERCOAT FINISHES CAN BE SPECIFIED FOR YOUR PROJECT NEEDS.

LaCANTINA DOORS OFFERS CUSTOM COLOR MATCHING TO VIRTUALLY ANY COLOR.

THESE 6 POPULAR DECORAL WOOD GRAIN POWDERCOAT FINISHES ARE AVAILABLE. CONTACT US FOR THE COMPLETE RANGE.

REAL WOOD LOOK



DARK CHERRY

ALUMINUM WOOD SYSTEMS LaCANTINADOORS.com

^{*}ACTUAL COLORS WILL VARY FROM THE PRINT. PLEASE REQUEST PAINT SWATCH SAMPLES

SIZING

OUR BIFOLD DOOR SYSTEMS ARE AVAILABLE IN THE MOST POPULAR SIZES AND OPENINGS.

Lacantina doors popular standard sizes are 7' and 8' tall and 9', 12', 15' and 18' wide with a 35" panel width. We specialize in custom "made to measure" systems which are available up to 52' wide and 10' tall with a maximum panel width of 39".

CONFIGURATIONS

Lacantina doors bifold door systems offer a range of configurations up to 16 panels, 8 in each direction, including a 90° zero post system.

VISIT WWW.LACANTINADOORS.COM FOR THE COMPLETE CONFIGURATION CHART AND LISTING OR CONTACT US TO DISCUSS HOW OUR DOOR SYSTEMS CAN MEET YOUR PROJECT NEEDS.

SILL CONSIDERATIONS

Lacantina doors offers a choice of sill options that perform for a range of conditions. Identify what sill option and floor transition best meet your needs.



THE **WEATHER RESISTANT** SILL IS OUR STANDARD SILL OPTION AND PROVIDES EFFECTIVE WEATHER SEALING FOR EXTERIOR APPLICATIONS SIMILAR TO RAISED SILLS TYPICAL OF SLIDING OR SWINGING PATIO DOORS. THE SILL IS INSTALLED ON TOP OF THE SUB FLOOR AND THEN THE FINISHED FLOOR IS BUILT UP ON THE INTERIOR. RECESSING THE WEATHER RESISTANT SILL PROVIDES A MINIMAL TRANSITION FROM INSIDE TO OUTSIDE WITH EFFECTIVE WEATHER SEALING. IN THIS APPLICATION, THE SILL IS INSTALLED INTO THE SUB FLOOR AND ALLOWS THE INTERIOR FINISH FLOOR TO BE LEVEL WITH THE INTERIOR SILL STOP.



THE ZERO STEP SILL IS OUR PROPRIETARY DESIGN THAT OFFERS A SEAMLESS TRANSITION FOR SAME INTERIOR TO EXTERIOR FLOOR LEVELS. THE CONTINUOUS DRAFT GUARD SEAL ELIMINATES THE NEED FOR DOOR MOUNTED SWEEPS AND EFFECTIVELY CLOSES THE GAP USUALLY FOUND UNDERNEATH THE DOORS BASED ON FLOOR CONDITIONS AND DOOR ADJUSTMENT. WHEN THE DOORS ARE CLOSED, THE DRAFT GUARD IS ROTATED INTO THE RAISED POSITION AND PROTECTS AGAINST WIND DRAFTS AND WEATHER. WHEN THE DOORS ARE OPENED, THE DRAFT GUARD SEAL DROPS DOWN FLUSH WITH THE FINISHED FLOOR AND CREATES THE ULTIMATE INDOOR/OUTDOOR EXPERIENCE. THE ZERO STEP SILL IS RECOMMENDED FOR WEATHER PROTECTED OPENINGS.



THE GUIDE CHANNEL SILL OPTION IS RECOMMENDED FOR INTERIOR APPLICATIONS WHEN FLOOR LEVELS ARE THE SAME. IT IS NOT SUITABLE FOR EXTERIOR USE UNLESS AIR INFILTRATION IS ACCEPTABLE OR THERE IS NO RISK OF WATER INFILTRATION.



THE COMMERCIAL SILL IS ADA COMPLIANT AND IS AN OPTION WHEN INTERIOR AND EXTERIOR FLOOR LEVELS ARE THE SAME AND A MAXIMUM SILL HEIGHT FROM FINISH FLOOR OF 1/2" IS REQUIRED. ADEQUATE OVERHANGS ARE RECOMMENDED TO REDUCE THE RISK OF WATER INFILTRATION.